

SPECIFICATIONS

MODELS		BC5060	BC5070
Bale chamber			
Width	(cm)	46	46
Height	(cm)	36	36
Length	(cm)	31 - 132	31 - 132
Tractor requirements			
Minimum PTO power	(kW/hp)	34/45	45/60
PTO speed	(rpm)	540	540
Hydraulic distributors		1	1
Main drive			
Gearbox		Oil immersed, hypoid with tapered roller bearings	
Protection		Shearbolt, overrunning clutch and slip clutch	
Power-Pivot support		●	●
Pick-up			
Overall width including flare	(cm)	180	200
Number of tine bars		6	6
Number of spring tines		132	156
Hydraulic pick-up lift		●	●
Gauge wheel	(size)	3.00x12 (Semi-pneumatic)	15x6.00x6 (Flotation)
Hydraulic tongue swing		○	○
Feeder			
Opening	(cm ²)	1826	1826
Type		Rotary	Rotary
Plunger			
Speed	(stokes/min)	93	93
Stroke length	(cm)	76	76
Bale density control			
Manual tension springs		●	●
Hydroformatic system		○	○
Knotter			
Drive		Shaft / gear	Shaft / gear
Protection		Shearbolt	Shearbolt
Twine capacity		6 balls	6 balls
Knotter lubrication		Centralised hand pump	Centralised hand pump
Tyres			
Left	(size)	27x9.50-15 (6 ply)	31x13.50-15 (6 ply)
Right	(size)	27x9.50-15 (6 ply)	31x13.50-15 (6 ply)
Baler dimensions and weight			
Length (without chute)	(cm)	520	520
Width	(cm)	279	304
Height	(cm)	178	180
Weight	(kg)	1540	1620

● Standard ○ Optional – Not available



YOUR SUCCESS - OUR SPECIALTY

AT YOUR OWN DEALER

Visit our web site: www.newholland.co.nz

The data indicated in this folder are approximate. The models described here can be subjected to modifications without any notice by the manufacturer. The drawings and photos may refer to equipment that is either optional or intended for other countries. Please apply to our Sales Network for any further information. Published by New Holland Brand Communications. Bts Adv. - Printed in New Zealand - 03/09 - TP01 - 83001/NZ