

Models	BR6080	BR6090 - BR6090 Combi
Bale size		
Bale width / Bale diameter	(m) 1.20 / 1.25	1.20 / 1.25
Volume	(m ³) 1.47	1.47
Pick-up		
Width	(m) 1.50 / 2.00	2.00
Number of tines / tine bars	90 / 5 - 112 / 4	112 / 4
Windguard	tines / plate & tines	plate & tines
Windguard roller kit	–	○
Pick-up wheels, 15 x 6.00-6-4ply	○ / ●	●
Protection	shearbolt	shearbolt
Hydraulic pick-up lift	○ / ●	●
Feeding		
Type	– / Crank type	Rotor type
Rotor reverser kit	–	○ / ●
Number of augers	2	2
Feeder width	(m) – / 140	140
CropCutter™		
Number of knives	–	15 (maximum)
Knife range choice	–	15 / 7 / 8 / 0
CropCutter engagement	–	Bale Command Plus
Knife protection	–	Spring
Rotor reverser kit	–	○
Bale formation		
Type	Roll-Bar system	Roll-Bar system
Rollers	1 bottom roll	1 bottom roll & 1 starter roll
Number of bale rotation bars	36	34
Wrapping		
Type	Twin Twine System	Bale Command Plus
Control	Twin driven	Electric
Number of twines	2	2
Twine wrapping patterns		
Pre-programmed	3	3
Customer programmed	–	1
Number of twine balls	5	5
Net wrapping	–	Duckbill type
Net, number of wraps	–	Variable, 1 / 4 wraps
Net storage	–	1 active, 2 stored
Silage wrapper		
Film width	(mm) –	750
Number of wrapping arms	–	2
Pre-stretch	–	70%, adjustable
Hydraulic system	–	one single acting with free flow return
Oil flow min / max	(litres/min) –	20 / 30
Quater turn bale chute	–	– / ○
Baler dimensions		
Length, incl. bale ejector	(m) 4.05	3.95
Height	(m) 2.23	2.35
Width without pick-up wheels	(m) 2.37 / 2.40	2.40
Width with pick-up wheels	(m) 2.40 / 2.65	2.69
Weight	(kg) 1978 / 2244	2775 / 2800
Dimensions of the Combi		
Overall width	(m) –	2.75 (with 15.0/55-17 tyres)
Overall length / height	(m) – / –	6.20 / 2.80
Weight	(kg) –	4580
Tyres		
10.0/75 x 15.3 - 8 ply	● / –	–
11.5/80 x 15.3 - 8 ply	○	●
15.0/55 x 17 - 10 ply	–	○
19.0/45 x 17 - 10 ply	–	○
Other equipment		
Road light equipment	●	●
Automatic chain lubrication	○	●
Springloaded bale ejector	○	○